



Casoprano™ Product Informmation

International high quality standard

From the standard manufacturing processes with the good quality control process plus the initiative in modern design and pre-paint in-house to get the excellent quality decorative ceiling "Casoprano" which according to international standard

Qualification

- Premium quality with a wide range of modern patterns and textures
- Manufactured and pre-painted * in house and able to repainted
- · Various and modern designs
- · Light weight, quick and easy to install
- · Economic and budget saving (installation/labor cost)
- · Durable and long lasting
- Preventing heat transfer which reduce electricity consumption for air conditioning system
- Up to 30 minutes fire resistance
- High value of light reflectance LR>75% (LR1)
- Sound insulation property (CAC 38 dB)
- · Safe and environmentally friendly



Specification

Decorative ceiling tile with pre-paint in-house, Gyproc Casoprano

(CasoFINA, Caso STAR, CasoPIN, CasoMOON, CasoOCEAN, CasoROC):

The trim edge size 600x600 mm. and 595x595 mm. with 9 mm thickness.

The trim edge size 1200x600 mm. and 1195x595 mm. with 12 mm thickness.

The quality is complied with TIS 219-2552 and BS1230 standards. Easy installation by using the

Gyproc framing systems


Gyproc Grid 32

Gyproc Grid 38

Gyproc Grid 38T15


Technical Informmation

Description	BS1230 and TIS219-2552
Fire protection	Non-combustible material (class 0) comply with BS 476 Part 6 & &
Light reflectance	More than 75% (ASTM E 1477)
Thickness and size	9x595x595 mm. and 12x1195x595 mm. 9x600x600 mm. and 12x1200x600 mm.
Edge detail	Trim edge
Ceiling attenuation class (CAC)	38 dB









Room to room sound insulation Ceiling Attenuation Class Casoprano - CAC 38 dB

Tile Patterns

